



FEATURES


- Modular Basket Carousel Design to suit Oil & Gas and Offshore Wind Flexible/Umbilical/Cable Lay Markets.
- Single combined lift capability of Circular Base Grillage, Turntable, Hub and Drive System – reducing vessel and quayside mobilisation time.
- Low Profile Circular Grillage optimises vessel deck space enhancing its suitability for smaller offshore wind installation vessels.
- Hydraulic Drives / Controls can be integrated to spooling tensioner and deck tensioner to provide a fully synchronised, failsafe, lay spread.
- Can be offered as carousel only, or with dedicated spooling tower, and deck tensioner.

- 2000TE PRODUCT CAPACITY
- 15M BASKET OUTER DIAMETER
- 4.5M – 8M VARIABLE INNER HUB DIAMETER
- 6M BASKET HEIGHT (ADJUSTABLE)
- BASKET PARTITIONS AVAILABLE

2000Te BASKET CAROUSEL

SH-BC-2000

EQUIPMENT SPECIFICATIONS SHEET



Basket Dimensions can be adjusted to suit specific project requirements

→ **TECHNICAL DETAILS**

Dimensions

15m OD x 7.5m H

Assembled Weight [Empty]

15m - 257Te

→ **CAPABILITY**

Drive

2 x 140 kW Hydraulic Motors

Equipped with Failsafe Brakes

Speed

1000m/hr maximum lay rate

→ **POWER**

HPU

280 kW - Integrated into Loading Tower or Standalone

6m x 2.44m x 2.59m (20ft) Container

Required Supply

440V/400V, 60Hz/50Hz, 3 Phase

→ **OPTIONAL ANCILLARY EQUIPMENT**

Loading Tower c/w Spooling Tensioner

Deck Tensioner (See Individual Specification Sheets for info).

→ **CONTROLS**

Central Control Cabin Integrated with Loading Tower / Standalone if

Required – can also be linked to

Complete Lay Spread Control System

→ **LIFTING EQUIPMENT**

1 x Certified Lifting Rigging Set Supplied

1 x Spreader Bar Arrangement Supplied

(if lifting with 1500Te of product)

→ **CONNECTION PACKAGE**

1 x Hydraulic Hose & Power Cable Set Supplied

→ **DESIGN VERIFICATION**

Lloyds Register 2009 (CLAME)

www.swanhunter.com